

# Package ‘GeoRange’

October 12, 2022

**Type** Package

**Title** Calculating Geographic Range from Occurrence Data

**Version** 0.1.0

**Description** Calculates and analyzes six measures of geographic range from a set of longitudinal and latitudinal occurrence data. Measures included are minimum convex hull area, minimum spanning tree distance, longitudinal range, latitudinal range, maximum pairwise great circle distance, and number of X by X degree cells occupied.

**License** GPL-3

**LazyData** TRUE

**Imports** sp,proj4,raster,moments,stats,graphics,grDevices,velociraptor

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** James Boyle Developer [aut, cre]

**Maintainer** James Boyle Developer <jamesboy@buffalo.edu>

**Repository** CRAN

**Date/Publication** 2017-06-15 15:07:19 UTC

## R topics documented:

BivalvePBDB . . . . .	2
CellCount . . . . .	3
CHullArea . . . . .	4
CHullAreaEarth . . . . .	4
CoordCollapse . . . . .	5
CoordList_PBDB . . . . .	6
deg2rad . . . . .	7
EqualAreaRectangle . . . . .	7
GCD . . . . .	8
gcd_hf . . . . .	9
gcd_vif . . . . .	10
GeoCor . . . . .	11
GeoPerformance_SkewCV . . . . .	12

GeoRange_MultiTaxa . . . . .	13
GeoRarefaction_MultiTaxa . . . . .	14
GeoRarefaction_SingleTaxon . . . . .	15
hello . . . . .	17
HorseShoeArea . . . . .	17
LatRg . . . . .	18
LongRg . . . . .	18
MSTDist . . . . .	19
MSTDist_FromMat . . . . .	20
PEE_MultiTaxa . . . . .	21
PEE_SingleTaxon . . . . .	22
PlotConvexHull . . . . .	23
PlotMST . . . . .	23
Plot_Rarefaction . . . . .	24
PtsAlgHorseShoe . . . . .	25
PWMatrix . . . . .	26
RandHorseShoe . . . . .	27
RandRec . . . . .	28
<b>Index</b>	<b>29</b>

---

BivalvePBDB	<i>Occurrence data on bivalves from the Ypresian Data from the Paleobiology Database via the velociraptr package on May 17th, 2017</i>
-------------	--

---

## Description

Occurrence data on bivalves from the Ypresian Data from the Paleobiology Database via the velociraptr package on May 17th, 2017

## Usage

```
data(BivalvePBDB)
```

## Format

A csv file

## Examples

```
data(BivalvePBDB)
```

---

CellCount	<i>Calculates degree x degree cell counts of a specified size</i>
-----------	---

---

**Description**

Calculates degree x degree cell counts of a specified size

**Usage**

```
CellCount(longs, lats, CellSize = 5, longBounds = c(-180, 180),  
          latBounds = c(-90, 90))
```

**Arguments**

longs	- Array of longitudinal occurrence values in decimal degrees
lats	- Array of latitudinal occurrence values in decimal degrees
CellSize	- Size of each cell in degree X degree
longBounds	- Array of longitudinal boundaries in decimal degrees
latBounds	- Array of latitudinal boundaries in decimal degrees

**Value**

Returns the number of cells occupied, specified cell size, and coordinate list

**Note**

This method uses grids cells constructed by equal degrees not area. So high latitude cells will have smaller areas than those at low latitude

**Examples**

```
longs<-c(22,55,-144)  
lats<-c(-12,22,-12)  
CellCount(longs,lats,CellSize=5,longBounds=c(-180,180),latBounds=c(-90,90))
```

---

CHullArea	<i>Performs Convex Hull area calculation</i>
-----------	--

---

**Description**

Performs Convex Hull area calculation

**Usage**

```
CHullArea(longs, lats)
```

**Arguments**

longs	- Array of longitudinal occurrence values in decimal degrees
lats	- Array of latitudinal occurrence values in decimal degrees

**Details**

Uses the cylindrical equal area projection in order to check if the minimum convex hull wraps around the prime meridian

**Value**

Returns area of a set of coordinates

**Note**

Relies on the 'sp' package for the Polygon and chull function

**Examples**

```
longs<-c(-12,23,55)
lats<-c(34,22,30)
CHullArea(longs,lats)
```

---

CHullAreaEarth	<i>Performs convex hull area calculation from coordinate sets on the Earth's surface</i>
----------------	--

---

**Description**

Performs convex hull area calculation from coordinate sets on the Earth's surface

**Usage**

```
CHullAreaEarth(longs, lats)
```

**Arguments**

longs - Longitudinal coordinates of occurrences in decimal degrees  
lats - Latitudinal coordinates of occurrences in decimal degrees

**Details**

Uses the cylindrical equal area projection in order to check if the minimum convex hull wraps around the prime meridian

**Value**

Returns the convex hull area in square kilometers

**Note**

Relies on the 'sp' package for the Polygon and chull function. Assumes latitude and longitude coordinates use the WGS84 datum

**Examples**

```
longs<-c(-133,-101,56)
lats<-c(33,12,-2)
CHullAreaEarth(longs,lats)
```

---

CoordCollapse	<i>Removes duplicate geographic locations and binds coordinates into a single element</i>
---------------	---

---

**Description**

Removes duplicate geographic locations and binds coordinates into a single element

**Usage**

```
CoordCollapse(longs, lats)
```

**Arguments**

longs - Longitudinal coordinates of occurrences in decimal degrees  
lats - Latitudinal coordinates of occurrences in decimal degrees

**Value**

Returns a 2-column array of coordinates without any duplicate locations

**Note**

Points are truncated to the hundredths place before checking for duplicates

**Examples**

```
longs<-c(34, 133, -45)
lats<-c(-12, 44, 76)
CoordCollapse(longs, lats)
```

---

CoordList_PBDB	<i>Creates an occurrence matrix of taxa by coordinates from the Paleobiology Database</i>
----------------	---

---

**Description**

Creates an occurrence matrix of taxa by coordinates from the Paleobiology Database

**Usage**

```
CoordList_PBDB(pbdb_data)
```

**Arguments**

pbdb\_data - Matrix of occurrence records from the Paleobiology Database, see downloadPBDB function in velociraptr package

**Details**

Cuts out records for which there is no paleogeographic information known

**Value**

Returns a taxa by coordinates matrix of occurrences

**See Also**

See the velociraptr package for more details on downloading PBDB data

**Examples**

```
data(BivalvePBDB)
CoordList_PBDB(BivalvePBDB)
```

---

deg2rad	<i>Converts degrees to radians</i>
---------	------------------------------------

---

**Description**

Converts degrees to radians

**Usage**

```
deg2rad(deg)
```

**Arguments**

deg - decimal degree to be converted to radians

**Value**

Returns the degree in radians

**References**

[1]Originally from <http://www.r-bloggers.com/great-circle-distance-calculations-in-r/>

**Examples**

```
deg2rad(45)
```

---

EqualAreaRectangle	<i>Create a rectangular shaped distribution with equal area to a given area</i>
--------------------	---

---

**Description**

Create a rectangular shaped distribution with equal area to a given area

**Usage**

```
EqualAreaRectangle(center = c(0, 0), TargetArea, error = 0.001)
```

**Arguments**

center - Array containing the coordinates of the center of circular portion of the rectangle in decimal degree

TargetArea - Area in square kilometers desired for the rectangle

error - The tolerable proportion of error between the rectangular shape and the TargetArea

**Value**

Returns a 2-dimensional array of decimal degree coordinates outlining a rectangular shaped distribution

**Note**

This returns 100 evenly spaced points along each corner of the rectangle, in addition to the corners themselves

**Examples**

```
HorseShoeTest<-PtsAlgHorseShoe(z=2000,spacing=1,endAngles=c(-90,90))
HorseShoePts<-RandHorseShoe(center=c(0,0),npts=100,HorseShoeShape=HorseShoeTest)
EqualAreaRectangle(TargetArea=as.numeric(HorseShoePts$TotalArea_km2),error=0.001)
```

---

GCD	<i>Calculates the maximum pairwise great circle distance from a set of decimal degree coordinates</i>
-----	---

---

**Description**

Calculates the maximum pairwise great circle distance from a set of decimal degree coordinates

**Usage**

```
GCD(longs, lats)
```

**Arguments**

longs           - Longitudinal coordinates of occurrences in decimal degrees  
lats             - Latitudinal coordinates of occurrences in decimal degrees

**Details**

Because this function does not account for the possibility that a taxa may wrap around more than half the Earth the maximum value is half the circumference of the Earth, approximately 20,038 kilometers.

**Value**

Returns the maximum great circle distance in kilometers

**Note**

The great circle distance can be extracted from the result of a minimum spanning tree calculation MSTDist() if available to avoid redundant calculations



**Examples**

```
longs<-c(34,156,-78)
lats<-c(45,12,9)
GCD(longs,lats)
```

---

gcd_hf	<i>Calculates the geodesic distance between two points specified by latitude and longitude using the Haversine formula</i>
--------	--

---

**Description**

Calculates the geodesic distance between two points specified by latitude and longitude using the Haversine formula

**Usage**

```
gcd_hf(long1, lat1, long2, lat2)
```

**Arguments**

long1	- Longitudinal value of first point in decimal degrees
lat1	- Latitudinal value of first point in decimal degrees
long2	- Longitudinal value of second point in decimal degrees
lat2	- Latitudinal value of second point in decimal degrees

**Details**

The Haversine formula can be inaccurate depending on coordinates

**Value**

Returns the distance between two points on the Earth in kilometers

**Note**

The haversine method is inaccurate and should only be used when the Vincenty formula fails or over very small distances

**References**

[1] Adapted from <http://www.r-bloggers.com/great-circle-distance-calculations-in-r/>

**Examples**

```
long1<-22
lat1<-44
long2<-52
lat2<-51
gcd_hf(long1,lat1,long2,lat2)
```

---

gcd_vif	<i>Calculates the geodesic distance between two points specified by latitude/longitude using Vincenty inverse formula for ellipsoids</i>
---------	--

---

**Description**

Calculates the geodesic distance between two points specified by latitude/longitude using Vincenty inverse formula for ellipsoids

**Usage**

```
gcd_vif(long1, lat1, long2, lat2)
```

**Arguments**

long1	- Longitudinal value of first point in decimal degrees
lat1	- Latitudinal value of first point in decimal degrees
long2	- Longitudinal value of second point in decimal degrees
lat2	- Latitudinal value of second point in decimal degrees

**Value**

Returns the distance between two points on the Earth in kilometers

**References**

[1] Adapted from <http://www.r-bloggers.com/great-circle-distance-calculations-in-r/>

**Examples**

```
long1<-22
lat1<-44
long2<-52
lat2<-51
gcd_vif(long1,lat1,long2,lat2)
```

---

GeoCor	<i>Function to calculate the correlation coefficient for pairwise comparisons between geographic range measures</i>
--------	---

---

**Description**

Function to calculate the correlation coefficient for pairwise comparisons between geographic range measures

**Usage**

```
GeoCor(GeoRange, Start = 1, method = "pearson")
```

**Arguments**

GeoRange	- A matrix of taxa by geographic range calculations, as from the GeoRange_MultiTaxa function
Start	- The column index value where geographic range measures to be compared starts
method	- The correlation method to be used. See the cor() function for available inputs

**Value**

Returns a sparse pairwise matrix of correlation coefficients

**Note**

The correlation calculation uses the "pairwise.complete.obs" option from the cor function so that only complete pairs of observations are used, pairs containing an NA are ignored

**See Also**

See the velociraptr package for details of the downloadPBDB() function

**Examples**

```
## Not run:  
data(BivalvePBDB)  
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)  
testBivalve<-GeoRange_MultiTaxa(OccMatrix=BivalveMatrix,TaxaStart=3)  
GeoCor(testBivalve,Start=1,method="kendall")  
  
## End(Not run)
```

---

GeoPerformance\_SkewCV *Function to calculate the skewness and coefficient of variance for a set of geographic range calculations*

---

### Description

Function to calculate the skewness and coefficient of variance for a set of geographic range calculations

### Usage

```
GeoPerformance_SkewCV(GeoRange)
```

### Arguments

GeoRange - Data matrix containing the geographic range calculations for a set of taxa, as from the GeoRange\_MultiTaxa() function

### Value

Returns a list of the skewness and coefficient of variance for each geographic range measure

### Note

The coefficient of variance returned is standard deviation/mean

### See Also

See the raster and moments packages for more details on the calculation of skewness and coefficient of variance

### Examples

```
## Not run:  
data(BivalvePBDB)  
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)  
BivalveGeo<-GeoRange_MultiTaxa(OccMatrix=BivalveMatrix, TaxaStart=3)  
GeoPerformance_SkewCV(BivalveGeo)  
  
## End(Not run)
```

---

GeoRange_MultiTaxa	<i>Function to tabulate number of occurrences/locations, six geographic range measures, minimum and maximum latitude and longitude for each taxon in a dataset</i>
--------------------	--

---

### Description

Function to tabulate number of occurrences/locations, six geographic range measures, minimum and maximum latitude and longitude for each taxon in a dataset

### Usage

```
GeoRange_MultiTaxa(OccMatrix, TaxaStart, LongPos = 1, LatPos = 2,  
  CellSize = 5, longBounds = c(-180, 180), latBounds = c(-90, 90))
```

### Arguments

OccMatrix	- A matrix where columns are taxon occurrences and also having at least longitude and latitude values
TaxaStart	- The column index value where taxon records start
LongPos	- The column index value of longitudinal coordinates in the OccMatrix
LatPos	- The column index value of latitudinal coordinates in the OccMatrix
CellSize	- The size of each cell in degree X degree
longBounds	- Array of longitudinal boundaries in decimal degrees
latBounds	- Array of latitudinal boundaries in decimal degrees

### Value

Returns a matrix of taxa by geographic range measures, including number of observations, number of unique locations observed at, minimum spanning tree distance, minimum convex hull area, maximum pairwise great circle distance, latitudinal range, longitudinal range, and number of degree X degree cells occupied

### Note

Calculates the number of observations, localities, minimum spanning tree distance, convex hull area, longitudinal range, latitudinal range, and cell count

### See Also

See the `velociraptr` package for details of the `downloadPBDB()` function

**Examples**

```
## Not run:
data(BivalvePBDB)
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)
GeoRange_MultiTaxa(OccMatrix=BivalveMatrix,TaxaStart=3)

## End(Not run)
```

---

GeoRarefaction\_MultiTaxa

*Calculates six geographic range measures at resampled a number of time from specified sample sizes*

---

**Description**

Calculates six geographic range measures at resampled a number of time from specified sample sizes

**Usage**

```
GeoRarefaction_MultiTaxa(nLocCut = 3, OccMatrix, TaxaStart, LongPos = 1,
  LatPos = 2, iter = 10, CellSize = 5, longBounds = c(-180, 180),
  latBounds = c(-90, 90), steps = c(1, 50, 40, 30, 20, 10, 5),
  replacePts = FALSE)
```

**Arguments**

nLocCut	- The minimum number of locations a taxon must be seen at to have geographic range measures calculated
OccMatrix	- A matrix where columns are taxon occurrences and also having at least longitude and latitude values
TaxaStart	- The column index value where taxon records start
LongPos	- The column index value of longitudinal coordinates in the OccMatrix
LatPos	- The column index value of latitudinal coordinates in the OccMatrix
iter	- The number of times a taxon's locations are resampled at each step size
CellSize	- The size of each cell in degree X degree
longBounds	- Array of longitudinal boundaries in decimal degrees
latBounds	- Array of latitudinal boundaries in decimal degrees
steps	- Array of the values representing the number of points to be subsampled for each taxon
replacePts	- A logical value indicating whether points are allowed to be sampled more than once during each subsampling iteration

**Details**

The nLocCut parameter is the minimum number of distinct geographic locations a taxon must be observed at to have geographic range measures calculated, if below returns NA. The steps parameter typically begins with a 1 representing that all points should be used in calculations but this is not required. The replacePts parameter must be set to TRUE if any of the steps require a greater number of points to be sampled than there are actual locations for a taxon, otherwise the function will fail.

**Value**

Returns a vector where each element is a taxon with a list of each geographic range measure as a separate matrix of values. Measures include minimum spanning tree distance, minimum convex hull area, maximum pairwise great circle distance, latitudinal range, longitudinal range, and number of degree X degree cells occupied.

**Note**

If PEE values are to be calculated as a next step the steps parameter needs to have a value of 1 as its first value

**See Also**

See the velociraptor package for details of the downloadPBDB() function

**Examples**

```
## Not run:
data(BivalvePBDB)
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)
GeoRarefaction_MultiTaxa(nLocCut=20,OccMatrix=BivalveMatrix,TaxaStart=3,replacePts=TRUE)

## End(Not run)
```

---

GeoRarefaction\_SingleTaxon

*Calculates six geographic range measures at specified sample sizes for a single taxon*

---

**Description**

Calculates six geographic range measures at specified sample sizes for a single taxon

**Usage**

```
GeoRarefaction_SingleTaxon(TName = "Bird1", OccMatrix, LongPos = 1,
  LatPos = 2, iter = 10, CellSize = 5, longBounds = c(-180, 180),
  latBounds = c(-90, 90), steps = c(1, 50, 40, 30, 20, 10, 5),
  replacePts = FALSE)
```

**Arguments**

TName	- The name of the taxon of interest, as labeled in OccMatrix, as a string
OccMatrix	- A matrix where columns are taxon occurrences and also having at least longitude and latitude values
LongPos	- The column index value of longitudinal coordinates in the OccMatrix
LatPos	- The column index value of latitudinal coordinates in the OccMatrix
iter	- The number of times a taxon's locations are resampled at each step size
CellSize	- The size of each cell in degree X degree
longBounds	- Array of longitudinal boundaries in decimal degrees
latBounds	- Array of latitudinal boundaries in decimal degrees
steps	- Array of the values representing the number of points to be subsampled for each taxon
replacePts	- A logical value indicating whether points are allowed to be sampled more than once during each subsampling iteration

**Details**

The nLocCut parameter is the minimum number of distinct geographic locations a taxon must be observed at to have geographic range measures calculated, if below returns NA. The steps parameter typically begins with a 1 representing that all points should be used in calculations but this is not required. The replacePts parameter must be set to TRUE if any of the steps require a greater number of points be locations be sampled than are available for a taxon, otherwise the function will fail.

**Value**

Returns a list of each geographic range measure as a separate matrix of values. Measures include minimum spanning tree distance, minimum convex hull area, maximum pairwise great circle distance, latitudinal range, longitudinal range, and number of degree X degree cells occupied.

**Note**

If PEE values are to be calculated as a next step the steps parameter needs to have a value of 1 as its first value

**Examples**

```
## Not run:
data(BivalvePBDB)
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)
GeoRarefaction_SingleTaxon(TName=names(BivalveMatrix)[3],OccMatrix=BivalveMatrix,replacePts=TRUE)

## End(Not run)
```



---

hello	<i>Prints Hello, world!</i>
-------	-----------------------------

---

**Description**

Prints Hello, world!

**Usage**

```
hello()
```

**Value**

Prints 'Hello, world!'

---

HorseShoeArea	<i>Function to calculate the area of a given horseshoe shape</i>
---------------	--

---

**Description**

Function to calculate the area of a given horseshoe shape

**Usage**

```
HorseShoeArea(HorseShoeShape)
```

**Arguments**

HorseShoeShape - Object containing the outline of a horseshoe shape, output from PtsAlgHorseShoe function

**Value**

Returns the area of the horseshoe shape with the circular and rectangular portions separated

**Note**

Currently forces use of a height  $5/4$  width and  $r_2=2*r_1$  of origin (center)

**References**

[1] From <http://mathforum.org/library/drmath/view/51816.html>

**Examples**

```
HorseShoeTest<-PtsAlgHorseShoe(z=2000, spacing=1, endAngles=c(-90, 90))  
HorseShoeArea(HorseShoeTest)
```

---

LatRg	<i>Calculates the latitudinal range in degrees and kilometers</i>
-------	---

---

**Description**

Calculates the latitudinal range in degrees and kilometers

**Usage**

```
LatRg(lats)
```

**Arguments**

lats                   - Latitudinal occurrences in decimal degrees

**Value**

Returns the outermost coordinates of the set, the latitudinal span in degrees and in kilometers

**Examples**

```
lats<-c(-23,56,-2,45,66)
LatRg(lats)
```

---

LongRg	<i>Calculates the longitudinal range in degrees and kilometers, assuming a latitude of 45 degrees for all points by default. Accounts for the possibility of wrapping around the globe.</i>
--------	---

---

**Description**

Calculates the longitudinal range in degrees and kilometers, assuming a latitude of 45 degrees for all points by default. Accounts for the possibility of wrapping around the globe.

**Usage**

```
LongRg(longs, lats = 45)
```

**Arguments**

longs                   - Longitudinal occurrences in decimal degrees  
lats                    - A single value representing the latitude to calculate longitudinal distance from or a list of latitudinal coordinates in decimal degrees

**Details**

Calculates the longitudinal range as 360-largest longitudinal gap and accounts for the possibility that a taxon's range wraps around the prime meridian

**Value**

Returns the outermost coordinates of the set, the longitudinal span in degrees and in kilometers

**Examples**

```
longs<-c(133,76,-77,7,-80)
lats<-c(45)
LongRg(longs)
```

---

MSTDist	<i>Calculates the minimum spanning tree distance, in kilometers, using Prim's Algorithm [1]</i>
---------	---

---

**Description**

Calculates the minimum spanning tree distance, in kilometers, using Prim's Algorithm [1]

**Usage**

```
MSTDist(longs, lats)
```

**Arguments**

longs           - Longitudinal occurrences in decimal degrees  
lats            - Latitudinal occurrences in decimal degrees

**Details**

Uses Prim's algorithm for finding the minimum spanning tree, time-consuming calculation as the number of locations increases past 1000

**Value**

Returns the minimum spanning tree distance in kilometers, the pairwise distance matrix of occurrences, the order points were connected in, and a 2-column array of coordinates

**References**

[1] Prim, R.C. 1957. Shortest Connection Networks and Some Generalizations. The Bell System Technical Journal 36:1389-1401.

**Examples**

```
longs<-c(12, 34, -55)
lats<-c(-41, 3, 56)
MSTDist(longs,lats)
```

---

MSTDist_FromMat	<i>Calculates the minimum spanning tree distance, in kilometers, using Prim's Algorithm [1] and a previously calculated pairwise distance matrix</i>
-----------------	--

---

**Description**

Calculates the minimum spanning tree distance, in kilometers, using Prim's Algorithm [1] and a previously calculated pairwise distance matrix

**Usage**

```
MSTDist_FromMat(longs, lats, DistMat)
```

**Arguments**

longs	- Longitudinal occurrences in decimal degrees
lats	- Latitudinal occurrences in decimal degrees
DistMat	- Pairwise distance matrix of coordinates, from the PWMatrix() function

**Details**

Uses Prim's algorithm for finding the minimum spanning tree

**Value**

Returns the minimum spanning tree distance in kilometers, the pairwise distance matrix of occurrences, the order points were connected in, and a 2-column array of coordinates

**References**

[1] Prim, R.C. 1957. Shortest Connection Networks and Some Generalizations. The Bell System Technical Journal 36:1389-1401.

**Examples**

```
MSTCalc<-MSTDist(longs=c(22,44,-12,67),lats=c(-77,56,22,56))
MSTDist_FromMat(MSTCalc$Longitude,MSTCalc$Latitude,MSTCalc$MST_DistMat)
```

---

PEE_MultiTaxa	<i>Function to compile the PBDB_PEE_SingleTaxon output for a list of taxa</i>
---------------	---

---

### Description

Function to compile the PBDB\_PEE\_SingleTaxon output for a list of taxa

### Usage

```
PEE_MultiTaxa(GeoRare_Multi)
```

### Arguments

GeoRare\_Multi - The list of geographic range measures calculated from the GeoRarefaction\_MultiTaxa function

### Value

Returns a vector list of six geographic range measures matrix with percent error of estimates [1] for each value

### References

[1] Russell, M.P. & D.R. Lindberg. 1988. Real and Random Patterns Associated with Molluscan Spatial and Temporal Distributions. *Paleobiology* 14:322-330.

### See Also

See the `velociraptr` package for details of the `downloadPBDB()` function

### Examples

```
## Not run:  
data(BivalvePBDB)  
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)  
BivalveGeo<-GeoRarefaction_MultiTaxa(nLocCut=20,OccMatrix=BivalveMatrix,TaxaStart=3,replacePts=TRUE)  
PEE_MultiTaxa(BivalveGeo)  
  
## End(Not run)
```

---

PEE_SingleTaxon	<i>Function to calculate PEE [1] matrices for all the geographic range measures</i>
-----------------	---

---

**Description**

Function to calculate PEE [1] matrices for all the geographic range measures

**Usage**

```
PEE_SingleTaxon(GeoRare, TName = "Brach 1")
```

**Arguments**

GeoRare - The list of geographic range measures calculated from the GeoRarefaction\_SingleTaxon or GeoRarefaction\_MultiTaxa functions

TName - Name of the target taxon for analysis as a string

**Value**

Returns a list of six geographic range measures matrix with percent error of estimates for each value

**References**

[1] Russell, M.P. & D.R. Lindberg. 1988. Real and Random Patterns Associated with Molluscan Spatial and Temporal Distributions. Paleobiology 14:322-330.

**See Also**

See the velociraptr package for details of the downloadPBDB() function

**Examples**

```
## Not run:  
data(BivalvePBDB)  
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)  
BivalveGeo<-GeoRarefaction_MultiTaxa(nLocCut=50,OccMatrix=BivalveMatrix,TaxaStart=3,iter=20)  
PEE_SingleTaxon(GeoRare=BivalveGeo,TName=names(BivalveGeo)[3])  
  
## End(Not run)
```

---

PlotConvexHull                    *Plots the minimum convex hull of a set of coordinates*

---

**Description**

Plots the minimum convex hull of a set of coordinates

**Usage**

```
PlotConvexHull(xcoord, ycoord, lcolor = "blue")
```

**Arguments**

xcoord                    - Array of x-coordinates or longitudinal values  
ycoord                    - Array of y-coordinates or latitudinal values  
lcolor                    - String or integer value indicating the color of the convex hull boundary lines

**Value**

Plots a minimum convex hull

**Note**

This function does not account for the possibility of points crossing the prime meridian and in cases where this occurs the convex hull shown will be incorrect

**Examples**

```
longs<-c(20,20,40,40)
lats<-c(-5,5,-5,5)
PlotConvexHull(xcoord=longs,ycoord=lats)
```

---

PlotMST                    *Plots the minimum spanning tree of a set of coordinates*

---

**Description**

Plots the minimum spanning tree of a set of coordinates

**Usage**

```
PlotMST(MSTCalc, color = "black", symbol = 16, xlimit = "NA",
        ylimit = "NA")
```

**Arguments**

MSTCalc	- Output from the MSTDist function
color	- Color of the lines connecting point
symbol	- Symbol value for the pch graphical parameter for plotting coordinates
xlimit	- Array of values denoting the x-axis limits
ylimit	- Array of values denoting the y-axis limits

**Value**

Plots a minimum spanning tree

**Note**

If the xlimit and ylimit parameters are left to their default values the axis ranges are based on the minimum and maximum values of the coordinates This function does not account for the possibility of points crossing the prime meridian and in cases where this occurs lines will cut across the entire plot

**Examples**

```
w<-MSTDist(longs=c(23,78,-23,56),lats=c(21,4,55,-3))
PlotMST(MSTCalc=w)
```

---

Plot_Rarefaction	<i>Plots the measured value versus rarefied samples or percent error of estimates (PEE) of a rarefied samples for a geographic range measure</i>
------------------	--

---

**Description**

Plots the measured value versus rarefied samples or percent error of estimates (PEE) of a rarefied samples for a geographic range measure

**Usage**

```
Plot_Rarefaction(Mes1_AllTaxa, Mes2_AllTaxa, symbol = 20, measure = 2,
  SampSize = 1, color = "black")
```

**Arguments**

Mes1_AllTaxa	- Vector list of measured values for multiple taxa, from the GeoRarefaction_MultiTaxa function, or PEE calculations for multiple taxa, from from PEE_MultiTaxa function
Mes2_AllTaxa	- Vector list of measured values for multiple taxa, output from GeoRarefaction_MultiTaxa function
symbol	- Symbol used for plotting, as per pch graphical parameter



measure	- Specifies which measure to be plotted, 2=MST 3=CH 4=GCD 5=LatRg 6=LongRg 7=CellCount
SampSize	- Specifies the index value of the rarefaction sample size from the PEE_AllTaxa parameter
color	- Specifies the color of symbols being plotted

### Details

For each taxon for a specific geographic range measure using 95 Measure paramter is the ordinal position of the measure of interest 2=MST,3=CH,4=GCD,5=LatRg,6=LongRg,7=CellCount SampSize parameter indicates the index column position of steps size, default is first column (all points)

### Value

Returns a plot of measured geographic range values or PEE versus true value for a specific geographic range measure at varying sample sizes

### Examples

```
## Not run:
data(BivalvePBDB)
BivalveMatrix<-CoordList_PBDB(BivalvePBDB)
BivalveGeo<-GeoRarefaction_MultiTaxa(nLocCut=20,OccMatrix=BivalveMatrix,TaxaStart=3,replacePts=TRUE)
BivalvePEE<-PEE_MultiTaxa(BivalveGeo)
Plot_Rarefaction(BivalvePEE,BivalveGeo,symbol=20,measure=2,SampSize=2)

## End(Not run)
```

---

PtsAlgHorseShoe	<i>Function to find points along a horseshoe shape</i>
-----------------	--

---

### Description

Function to find points along a horseshoe shape

### Usage

```
PtsAlgHorseShoe(z, spacing = 1, endAngles = c(-90, 90))
```

### Arguments

z	- Distance in kilometers from the center of the horseshoe to its lower boundary
spacing	- Degrees between successive point outlining the horseshoe shape
endAngles	- Array of values denoting the degree of rotation for the circular part of the horseshoe distribution

**Details**

Currently forces use 0,0 as the center, a height 5/4 width, and  $r2=2*r1$  of origin (center)

**Value**

Returns a 2-dimensional array of decimal degree coordinates outlining a horseshoe shape

**Note**

Currently only works when endAngles are multiples of -90,90; otherwise rectangle point positions are off

**References**

[1] From <http://mathforum.org/library/drmath/view/51816.html>

**Examples**

```
PtsAlgHorseShoe(z=2000, spacing=1, endAngles=c(-90, 90))
```

---

 PWMatrix

*Creates a sparse pairwise distance matrix of a coordinate set*

---

**Description**

Creates a sparse pairwise distance matrix of a coordinate set

**Usage**

```
PWMatrix(Coords)
```

**Arguments**

Coords - Two-dimensional array of longitudinal and latitudinal coordinates output from CoordCollapse() function

**Value**

Returns a sparse pairwise distance matrix of great circle distances between pairs of points

**Examples**

```
longs<-runif(10, -22, 33)
lats<-runif(10, -22, 33)
Coords<-CoordCollapse(longs, lats)
PWMatrix(Coords)
```

---

RandHorseShoe	<i>Function to randomly generate points within a horseshoe-shape</i>
---------------	--

---

**Description**

Function to randomly generate points within a horseshoe-shape

**Usage**

```
RandHorseShoe(center = c(0, 0), npts = 100, HorseShoeShape, HRatio = 1.5,
  RadRatio = 0.5)
```

**Arguments**

center	- Array containint the coordinates of the center of circular portion of the horseshoe in decimal degrees
npts	- Integer value indicating the number of points to generate within the horseshoe shape
HorseShoeShape	- Object containing the outline of a horseshoe shape, output from PtsAlgHorseShoe function
HRatio	- The ratio of the lower rectangle portions of the horseshoe to the outer radius of the circular portion of the horseshoe
RadRatio	- The ration of the of the outer to inner radius of the circular part of the horseshoe shape

**Value**

Returns a 2-dimensional array of decimal degree coordinates within the horseshoe shape and the total area of the shape

**Note**

HRatio Currently defaults to 3/2 per the PtsAlgHorseShoe() function RadRatio currently defaults to 1/2 per the PtsAlgHorseShoe() function Center currently defaults to c(0,0) as this is always the center of the PtsAlgHorseShoe() function currently Function currently does not take account of the decreasing surface area moving toward the poles so points closer to the poles will be overrepresented relative to the actual surface area they represent

**Examples**

```
HorseShoeTest<-PtsAlgHorseShoe(z=2000, spacing=1, endAngles=c(-90,90))
RandHorseShoe(center=c(0,0), npts=100, HorseShoeShape=HorseShoeTest)
```

---

RandRec	<i>Function to randomly generate points within a given rectangular shaped distribution</i>
---------	--

---

**Description**

Function to randomly generate points within a given rectangular shaped distribution

**Usage**

```
RandRec(RecShape, npts = 100)
```

**Arguments**

RecShape	- The outline of a rectangular distribution output from the EqualAreaRectangle() function
npts	- The number of randomly generated points within the rectangular shape

**Value**

Returns a 2-dimensional array of decimal degree coordinates within a rectangular shape

**Note**

Function currently does not take account of the decreasing surface area moving toward the poles so points closer to the poles will be overrepresented relative to the actual surface area they represent

**Examples**

```
HorseShoeTest<-PtsAlgHorseShoe(z=2000,spacing=1,endAngles=c(-90,90))
HorseShoePts<-RandHorseShoe(center=c(0,0),npts=100,HorseShoeShape=HorseShoeTest)
RecOutline<-EqualAreaRectangle(TargetArea=as.numeric(HorseShoePts$TotalArea_km2),error=0.001)
RandRec(RecShape=RecOutline,npts=100)
```

# Index

## \* dataset

BivalvePBDB, [2](#)

BivalvePBDB, [2](#)

CellCount, [3](#)

CHullArea, [4](#)

CHullAreaEarth, [4](#)

CoordCollapse, [5](#)

CoordList\_PBDB, [6](#)

deg2rad, [7](#)

EqualAreaRectangle, [7](#)

GCD, [8](#)

gcd\_hf, [9](#)

gcd\_vif, [10](#)

GeoCor, [11](#)

GeoPerformance\_SkewCV, [12](#)

GeoRange\_MultiTaxa, [13](#)

GeoRarefaction\_MultiTaxa, [14](#)

GeoRarefaction\_SingleTaxon, [15](#)

hello, [17](#)

HorseShoeArea, [17](#)

LatRg, [18](#)

LongRg, [18](#)

MSTDist, [19](#)

MSTDist\_FromMat, [20](#)

PEE\_MultiTaxa, [21](#)

PEE\_SingleTaxon, [22](#)

Plot\_Rarefaction, [24](#)

PlotConvexHull, [23](#)

PlotMST, [23](#)

PtsAlgHorseShoe, [25](#)

PWMatrix, [26](#)

RandHorseShoe, [27](#)

RandRec, [28](#)