

Package ‘TPCselect’

June 29, 2023

Type Package

Title Variable Selection via Threshold Partial Correlation

Version 0.8.3

Author Cynthia Shao and Runze Li

Maintainer Cynthia Shao <cyny.shao@gmail.com>

Description A threshold partial correlation approach to selecting important variables in linear models of L. and others (2017) at <doi:10.5705/ss.202015.0473>, and in partial linear models of L. and others (2018) at <doi:10.1016/j.jmva.2018.06.005>. This package also extends the PC-simple algorithm of B. and others (2010) at <doi:10.1093/biomet/asq008> to partial linear models.

License GPL-3

Encoding UTF-8

RoxygenNote 7.2.1

Imports stats,corpcor,psych,MASS,KernSmooth

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Repository CRAN

Date/Publication 2023-06-29 13:00:06 UTC

R topics documented:

generate_toy_pdata	2
TPC	2
TPC_BIC	3
TPC_pl	4
TPC_pl_BIC	5
Index	7

`generate_toy_pldata` *A function to generate toy partial linear model data*

Description

A function to generate toy partial linear model data

Usage

```
generate_toy_pldata()
```

TPC

Variable Selection via Thresholded Partial Correlation

Description

These are the main selection functions with fixed significance level s and constant. The function TPC implements the thresholded partial correlation (TPC) approach to selecting important variables in linear models of Li et al. (2017). The function TPC_pl implements the thresholded partial correlation approach to selecting important variables in partial linear models of Liu et al. (2018). This function also extends the PC-simple algorithm of Bühlmann et al. (2010) to partial linear models.

Usage

```
TPC(y, x, s = 0.05, constant = 1, method = "threshold")
```

```
TPCselect(y, x, s = 0.05, constant = 1, method = "threshold")
```

Arguments

<code>y</code>	response vector;
<code>x</code>	covariate matrix;
<code>s</code>	a numeric value that used as significance level(s) for partial correlation test.
<code>constant</code>	a value that used as the tuning constant for partial correlation test. <code>constant</code> is treated as 1 when <code>method</code> is "simple".
<code>method</code>	the method to be used; default set as <code>method = "threshold"</code> ; "simple" is also available.

Value

TPC.object a TPC object, which extends the `lm` object. New attributes are:

- `beta` - the fitted coefficients
- `selected_index` - the selected coefficients indices

Examples

```

#generate sample data
p = 200
n = 200
truebeta <- c(c(3,1.5,0,0,2),rep(0,p-5))
rho = 0.3
sigma = matrix(0,p+1,p+1)
for(i in 1:(p+1)){
  for(j in 1:(p+1)){
    sigma[i,j] = rho^(abs(i-j))
  }
}
x_error = 0.9*MASS::mvrnorm(n,rep(0,p+1),sigma) + 0.1*MASS::mvrnorm(n,rep(0,p+1),9*sigma)
x = x_error[,1:p]
error = x_error[,p+1]
y = x%%truebeta + error

#perform variable selection via partial correlation
TPC.fit = TPC(y,x,0.05,1,method="threshold")
TPC.fit$beta

```

TPC_BIC

Variable Selection via Thresholded Partial Correlation

Description

Use BIC to select the best s and constant over grids.

Usage

```
TPC_BIC(y, x, s = 0.05, constant = 1, method = "threshold")
```

Arguments

<code>y</code>	response vector;
<code>x</code>	covariate matrix;
<code>s</code>	a value or a vector that used as significance level(s) for partial correlation test. BIC will be used to select the best s .
<code>constant</code>	a value or a vector that used as the tuning constant for partial correlation test. BIC will be used to select the best constant. <code>constant</code> is treated as 1 when method is "simple".
<code>method</code>	the method to be used; default set as <code>method = "threshold"</code> ; "simple" is also available.

Value

TPC.object a TPC object, which extends the lm object. New attributes are:

- beta - the fitted coefficients
- selected_index - the selected coefficients indices

Examples

```
#generate sample data
p = 200
n = 200
truebeta <- c(c(3,1.5,0,0,2),rep(0,p-5))
rho = 0.3
sigma = matrix(0,p+1,p+1)
for(i in 1:(p+1)){
  for(j in 1:(p+1)){
    sigma[i,j] = rho^(abs(i-j))
  }
}
x_error = 0.9*MASS::mvrnorm(n,rep(0,p+1),sigma) + 0.1*MASS::mvrnorm(n,rep(0,p+1),9*sigma)
x = x_error[,1:p]
error = x_error[,p+1]
y = x%%truebeta + error

#perform variable selection via partial correlation
TPC.fit = TPC_BIC(y,x,0.05,c(1,1.5),method="threshold")
TPC.fit$beta
```

 TPC_pl

Variable Selection via Thresholded Partial Correlation

Description

These are the main selection functions with fixed significance level s and constant. The function TPC implements the thresholded partial correlation (TPC) approach to selecting important variables in linear models of Li et al. (2017). The function TPC_pl implements the thresholded partial correlation approach to selecting important variables in partial linear models of Liu et al. (2018). This function also extends the PC-simple algorithm of Bühlmann et al. (2010) to partial linear models.

Usage

```
TPC_pl(y, x, u = NULL, s = 0.05, constant = 1, method = "threshold", ...)
```

Arguments

y	response vector;
x	covariate matrix;
u	non-parametric variable, should be a vector;
s	s is a numeric value or vector that used as the significance level(s) for the partial correlation tests
constant	a value that used as the tuning constant for partial correlation test. constant is treated as 1 when method is "simple".
method	the method to be used; default set as method = "threshold"; "simple" is also available.
...	smoothing parameters and functions: kernel, degree, and bandwidth h.

Value

TPC.object a TPC object, which extends the lm object. New attributes are:

- beta - the fitted coefficients
- selected_index - the selected coefficients indices

Examples

```
#generate partial linear data
samples <- generate_toy_pldata()
y <- samples[[1]]
x <- samples[[2]]
times <- samples[[3]]

#perform variable selection via partial correlation
TPC.fit = TPC_pl(y,x,times,0.05,1,method="threshold")
TPC.fit$beta
```

 TPC_pl_BIC

Variable Selection via Thresholded Partial Correlation

Description

Use BIC to select the best s and constant over grids.

Usage

```
TPC_pl_BIC(y, x, u = NULL, s = 0.05, constant = 1, method = "threshold", ...)
```

Arguments

y	response vector;
x	covariate matrix;
u	non-parametric variable, should be a vector;
s	a value or a vector that used as significance level(s) for partial correlation test. BIC will be used to select the best s.
constant	a value or a vector that used as the tuning constant for partial correlation test. BIC will be used to select the best constant. constant is treated as 1 when method is "simple".
method	the method to be used; default set as method = "threshold"; "simple" is also available.
...	smoothing parameters and functions: kernel, degree, and bandwidth h.

Value

TPC.object a TPC object, which extends the lm object. New attributes are:

- beta - the fitted coefficients
- selected_index - the selected coefficients indices

Examples

```
#generate partial linear data
samples <- generate_toy_pldata()
y <- samples[[1]]
x <- samples[[2]]
times <- samples[[3]]

#perform variable selection via partial correlation
TPC.fit = TPC_pl_BIC(y,x,times,0.05,c(1,1.5),method="threshold")
TPC.fit$beta
```

Index

`generate_toy_pldata`, 2

TPC, 2

TPC_BIC, 3

TPC_pl, 4

TPC_pl_BIC, 5

TPCselect (TPC), 2