

Package ‘binst’

October 12, 2022

Type Package

Title Data Preprocessing, Binning for Classification and Regression

Version 0.2.1

Date 2018-01-05

Author Chapman Siu

Maintainer Chapman Siu <chpmn.siu@gmail.com>

Description Various supervised and unsupervised binning tools including using entropy, recursive partition methods and clustering.

LazyData TRUE

Imports stats, rpart

Suggests discretization, Formula, testthat, BAMMtools, earth

RoxygenNote 5.0.1

License MIT + file LICENSE

URL <https://github.com/jules-and-dave/binst>

NeedsCompilation no

Repository CRAN

Date/Publication 2018-01-05 04:08:02 UTC

R topics documented:

create_bins	2
create_breaks	2
create_dtbreaks	3
create_earthbreaks	4
create_jenksbreaks	5
create_kmeansbreaks	5
create_mdldbks	6
get_control	7

Index	8
--------------	----------

create_bins	<i>Creates bins given breaks</i>
-------------	----------------------------------

Description

Creates bins given breaks

Usage

```
create_bins(x, breaks, method = "cuts")
```

Arguments

x	X is a numeric vector which is to be discretized
breaks	Breaks are the breaks for the vector X to be broken at. This excludes endpoints
method	the approach to bin the variable, can either be cuts or hinge.

Value

A vector same length as X is returned with the numeric discretization

See Also

[create_breaks](#)

Examples

```
create_bins(1:10, c(3, 5))
```

create_breaks	<i>A convenience function for creating breaks with various methods.</i>
---------------	---

Description

A convenience function for creating breaks with various methods.

Usage

```
create_breaks(x, y = NULL, method = "kmeans", control = NULL, ...)
```

Arguments

x	X is a numeric vector to be discretized
y	Y is the response vector used for calculating metrics for discretization
method	Method is the type of discretization approach used. Possible methods are: "dt", "entropy", "kmeans", "jenks"
control	Control is used for optional parameters for the method. It is a list of optional parameters for the function
...	instead of passing a list into control, arguments can be parsed as is.

Value

A vector containing the breaks

See Also

[get_control](#), [create_bins](#)

Examples

```
kmeans_breaks <- create_breaks(1:10)
create_bins(1:10, kmeans_breaks)

# passing the k means parameter "centers" = 4
kmeans_breaks <- create_breaks(1:10, list(centers=4))
create_bins(1:10, kmeans_breaks)

entropy_breaks <- create_breaks(1:10, rep(c(1,2), each = 5), method="entropy")
create_bins(1:10, entropy_breaks)

dt_breaks <- create_breaks(iris$Sepal.Length, iris$Species, method="dt")
create_bins(iris$Sepal.Length, dt_breaks)
```

create_dtbreaks *Create breaks using decision trees (recursive partitioning)*

Description

Create breaks using decision trees (recursive partitioning)

Usage

```
create_dtbreaks(x, y, control = NULL)
```

Arguments

x	X is a numeric vector to be discretized
y	Y is the response vector used for calculating metrics for discretization
control	Control is used for optional parameters for the method

Value

A vector containing the breaks

See Also

[create_breaks](#)

Examples

```
dt_breaks <- create_breaks(iris$Sepal.Length, iris$Species, method="dt")
create_bins(iris$Sepal.Length, dt_breaks)
```

create_earthbreaks *Create breaks using earth (i.e. MARS)*

Description

Create breaks using earth (i.e. MARS)

Usage

```
create_earthbreaks(x, y, control = NULL)
```

Arguments

x	X is a numeric vector to be discretized
y	Y is the response vector used for calculating metrics for discretization
control	Control is used for optional parameters for the method

Value

A vector containing the breaks

See Also

[create_breaks](#)

Examples

```
earth_breaks <- create_breaks(x=iris$Sepal.Length, y=iris$Sepal.Width, method="earth")
create_bins(iris$Sepal.Length, earth_breaks)
```

create_jenksbreaks *Create Jenks breaks*

Description

Create Jenks breaks

Usage

```
create_jenksbreaks(x, control = NULL)
```

Arguments

x X is a numeric vector to be discretized
control Control is used for optional parameters for the method

Value

A vector containing the breaks

See Also

[create_breaks](#)

Examples

```
jenks_breaks <- create_breaks(1:10, method="jenks")  
create_bins(1:10, jenks_breaks)
```

create_kmeansbreaks *Create kmeans breaks.*

Description

Create kmeans breaks.

Usage

```
create_kmeansbreaks(x, control = NULL)
```

Arguments

x X is a numeric vector to be discretized
control Control is used for optional parameters for the method

Value

A vector containing the breaks

See Also

[create_breaks](#)

Examples

```
kmeans_breaks <- create_breaks(1:10)
create_bins(1:10, kmeans_breaks)
```

create_mdldbks	<i>Create breaks using mdlp</i>
----------------	---------------------------------

Description

Create breaks using mdlp

Usage

```
create_mdldbks(x, y)
```

Arguments

x	X is a numeric vector to be discretized
y	Y is the response vector used for calculating metrics for discretization

Value

A vector containing the breaks

See Also

[create_breaks](#)

Examples

```
entropy_breaks <- create_breaks(1:10, rep(c(1,2), each = 5), method="entropy")
create_bins(1:10, entropy_breaks)
```

`get_control` *gets the default parameters for each method.*

Description

gets the default parameters for each method.

Usage

```
get_control(method = "kmeans", control = NULL)
```

Arguments

<code>method</code>	Method is the type of discretization approach used
<code>control</code>	Control are the controls for the algorithm

Value

List of default parameters

Index

`create_bins`, [2](#), [3](#)
`create_breaks`, [2](#), [2](#), [4-6](#)
`create_dtbreaks`, [3](#)
`create_earthbreaks`, [4](#)
`create_jenksbreaks`, [5](#)
`create_kmeansbreaks`, [5](#)
`create_mdldbks`, [6](#)

`get_control`, [3](#), [7](#)