

Package ‘primarycensored’

February 10, 2025

Title Primary Event Censored Distributions

Version 1.1.0

Description Provides functions for working with primary event censored distributions and 'Stan' implementations for use in Bayesian modeling. Primary event censored distributions are useful for modeling delayed reporting scenarios in epidemiology and other fields (Charniga et al. (2024) <[doi:10.48550/arXiv.2405.08841](https://doi.org/10.48550/arXiv.2405.08841)>). It also provides support for arbitrary delay distributions, a range of common primary distributions, and allows for truncation and secondary event censoring to be accounted for (Park et al. (2024) <[doi:10.1101/2024.01.12.24301247](https://doi.org/10.1101/2024.01.12.24301247)>). A subset of common distributions also have analytical solutions implemented, allowing for faster computation. In addition, it provides multiple methods for fitting primary event censored distributions to data via optional dependencies.

License MIT + file LICENSE

URL <https://primarycensored.epinowcast.org>,
<https://github.com/epinowcast/primarycensored>

BugReports <https://github.com/epinowcast/primarycensored/issues>

Depends R (>= 4.0.0)

Imports lifecycle, pracma, rlang

Suggests bookdown, cmdstanr, dplyr, fitdistrplus, knitr, ggplot2, rmarkdown, spelling, testthat (>= 3.1.9), usethis, withr

Additional_repositories <https://stan-dev.r-universe.dev>

Config/Needs/hexsticker hexSticker, sysfonts, ggplot2

Config/Needs/website r-lib/pkgdown, epinowcast/enwtheme

Config/testthat/edition 3

Encoding UTF-8

Language en-GB

LazyData true

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Sam Abbott [aut, cre, cph] (<<https://orcid.org/0000-0001-8057-8037>>),
 Sam Brand [aut] (<<https://orcid.org/0000-0003-0645-5367>>),
 Adam Howes [ctb] (<<https://orcid.org/0000-0003-2386-4031>>),
 James Mba Azam [ctb] (<<https://orcid.org/0000-0001-5782-7330>>),
 Carl Pearson [aut] (<<https://orcid.org/0000-0003-0701-7860>>),
 Sebastian Funk [aut] (<<https://orcid.org/0000-0002-2842-3406>>),
 Kelly Charniga [aut] (<<https://orcid.org/0000-0002-7648-7041>>)

Maintainer Sam Abbott <contact@samabbott.co.uk>

Repository CRAN

Date/Publication 2025-02-10 19:50:02 UTC

Contents

add_name_attribute	3
check_dprimary	4
check_pdist	5
check_truncation	5
dprimarycensored	6
expgrowth	8
fitdistdoublecens	10
new_pcens	12
pcd_as_stan_data	13
pcd_cmdstan_model	15
pcd_distributions	16
pcd_dist_name	16
pcd_load_stan_functions	17
pcd_primary_distributions	18
pcd_stan_dist_id	19
pcd_stan_files	19
pcd_stan_functions	20
pcd_stan_path	21
pcens_cdf	21
pcens_cdf.default	22
pcens_cdf.pcens_pgamma_dunif	23
pcens_cdf.pcens_plnorm_dunif	23
pcens_cdf.pcens_pweibull_dunif	24
pprimarycensored	25
rprimarycensored	27

Index

30

add_name_attribute *Helper method for custom distributions*

Description

[pprimarycensored\(\)](#) and related functions can identify which distributions are provided via the `pdist` and `dprimary` arguments when those are base R functions (e.g. `pnif`, `dexp`) via the `name` attribute.

Usage

```
add_name_attribute(func, name)
```

Arguments

<code>func</code>	Function, for example the p- or d- form of a distribution function.
<code>name</code>	Character string, starting with "p" or "d" indicating the underlying distribution.

Details

If you need to use a non-base R implementation, but know the distribution name, you can use this helper function to set it in a way that will be detected by [pprimarycensored\(\)](#) and related functions.

This is useful as it enables the automatic use of analytical solutions for distributions where they exist. You can check which analytical solutions are available using `methods(pcens_cdf)` and check distribution names using [pcd_dist_name\(\)](#).

Value

Function, with a "name" attribute added

See Also

Utility functions for working with distributions [pcd_dist_name\(\)](#), [pcd_distributions](#), [pcd_primary_distributions](#)

Examples

```
dist <- add_name_attribute(pnorm, "hello")
attr(dist, "name")
```

check_dprimary *Check if a function is a valid bounded probability density function (PDF)*

Description

This function tests whether a given function behaves like a valid PDF by checking if it integrates to approximately 1 over the specified range and if it takes the arguments min and max.

Usage

```
check_dprimary(dprimary, pwindow, dprimary_args = list(), tolerance = 0.001)
```

Arguments

dprimary	Function to generate the probability density function (PDF) of primary event times. This function should take a value x and a <code>pwindow</code> parameter, and return a probability density. It should be normalized to integrate to 1 over $[0, pwindow]$. Defaults to a uniform distribution over $[0, pwindow]$. Users can provide custom functions or use helper functions like <code>dexpgrowth</code> for an exponential growth distribution. See <code>primary_dists.R</code> for examples. The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply <code>add_name_attribute()</code> to yield properly tagged functions if they wish to leverage analytical solutions.
pwindow	Primary event window
dprimary_args	List of additional arguments to be passed to <code>dprimary</code> . For example, when using <code>dexpgrowth</code> , you would pass <code>list(min = 0, max = pwindow, r = 0.2)</code> to set the minimum, maximum, and rate parameters
tolerance	The tolerance for the integral to be considered close to 1

Value

NULL. The function will stop execution with an error message if `dprimary` is not a valid PDF.

See Also

Distribution checking functions `check_pdist()`, `check_truncation()`

Examples

```
check_dprimary(dunif, pwindow = 1)
```

check_pdist	<i>Check if a function is a valid cumulative distribution function (CDF)</i>
-------------	--

Description

This function tests whether a given function behaves like a valid CDF by checking if it's monotonically increasing and bounded between 0 and 1.

Usage

```
check_pdist(pdist, D, ...)
```

Arguments

pdist	Distribution function (CDF). The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply add_name_attribute() to yield properly tagged functions if they wish to leverage the analytical solutions.
D	Maximum delay (truncation point). If finite, the distribution is truncated at D. If set to Inf, no truncation is applied. Defaults to Inf.
...	Additional arguments to be passed to pdist

Value

NULL. The function will stop execution with an error message if pdist is not a valid CDF.

See Also

Distribution checking functions [check_dprimary\(\)](#), [check_truncation\(\)](#)

Examples

```
check_pdist(pnorm, D = 10)
```

check_truncation	<i>Check if truncation time is appropriate relative to the maximum delay</i>
------------------	--

Description

This function checks if the truncation time D is appropriate relative to the maximum delay. If D is much larger than necessary, it suggests considering setting it to Inf for better efficiency with minimal accuracy cost.

Usage

```
check_truncation(delays, D, multiplier = 2)
```

Arguments

delays	A numeric vector of delay times
D	The truncation time
multiplier	The multiplier for the maximum delay to compare with D. Default is 2.

Value

Invisible NULL. Prints a message if the condition is met.

See Also

Distribution checking functions [check_dprimary\(\)](#), [check_pdist\(\)](#)

Examples

```
check_truncation(delays = c(1, 2, 3, 4), D = 10, multiplier = 2)
```

dprimarycensored *Compute the primary event censored PMF for delays*

Description

This function computes the primary event censored probability mass function (PMF) for a given set of quantiles. It adjusts the PMF of the primary event distribution by accounting for the delay distribution and potential truncation at a maximum delay (D). The function allows for custom primary event distributions and delay distributions.

Usage

```
dprimarycensored(
  x,
  pdist,
  pwindow = 1,
  swindow = 1,
  D = Inf,
  dprimary = stats::dunif,
  dprimary_args = list(),
  log = FALSE,
  pdist_name = lifecycle::deprecated(),
  dprimary_name = lifecycle::deprecated(),
  ...
)

dpcens(
  x,
  pdist,
```

```

    pwindow = 1,
    swindow = 1,
    D = Inf,
    dprimary = stats::dunif,
    dprimary_args = list(),
    log = FALSE,
    pdist_name = lifecycle::deprecated(),
    dprimary_name = lifecycle::deprecated(),
    ...
)

```

Arguments

x	Vector of quantiles
pdist	Distribution function (CDF). The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply add_name_attribute() to yield properly tagged functions if they wish to leverage the analytical solutions.
pwindow	Primary event window
swindow	Secondary event window (default: 1)
D	Maximum delay (truncation point). If finite, the distribution is truncated at D. If set to Inf, no truncation is applied. Defaults to Inf.
dprimary	Function to generate the probability density function (PDF) of primary event times. This function should take a value x and a pwindow parameter, and return a probability density. It should be normalized to integrate to 1 over [0, pwindow]. Defaults to a uniform distribution over [0, pwindow]. Users can provide custom functions or use helper functions like <code>dexpgrowth</code> for an exponential growth distribution. See <code>primary_dists.R</code> for examples. The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply add_name_attribute() to yield properly tagged functions if they wish to leverage analytical solutions.
dprimary_args	List of additional arguments to be passed to dprimary. For example, when using <code>dexpgrowth</code> , you would pass <code>list(min = 0, max = pwindow, r = 0.2)</code> to set the minimum, maximum, and rate parameters
log	Logical; if TRUE, probabilities p are given as log(p)
pdist_name	[Deprecated] this argument will be ignored in future versions; use add_name_attribute() on pdist instead
dprimary_name	[Deprecated] this argument will be ignored in future versions; use add_name_attribute() on dprimary instead
...	Additional arguments to be passed to the distribution function

Details

The primary event censored PMF is computed by taking the difference of the primary event censored cumulative distribution function (CDF) at two points, $d + \text{swindow}$ and d . The primary event

censored PMF, $f_{\text{cens}}(d)$, is given by:

$$f_{\text{cens}}(d) = F_{\text{cens}}(d + \text{swindow}) - F_{\text{cens}}(d)$$

where F_{cens} is the primary event censored CDF.

The function first computes the CDFs for all unique points (including both d and $d + \text{swindow}$) using `pprimarycensored()`. It then creates a lookup table for these CDFs to efficiently calculate the PMF for each input value. For non-positive delays, the function returns 0.

If a finite maximum delay D is specified, the PMF is normalized to ensure it sums to 1 over the range $[0, D]$. This normalization can be expressed as:

$$f_{\text{cens, norm}}(d) = \frac{f_{\text{cens}}(d)}{\sum_{i=0}^{D-1} f_{\text{cens}}(i)}$$

where $f_{\text{cens, norm}}(d)$ is the normalized PMF and $f_{\text{cens}}(d)$ is the unnormalized PMF. For the explanation and mathematical details of the CDF, refer to the documentation of `pprimarycensored()`.

Value

Vector of primary event censored PMFs, normalized by D if finite (truncation adjustment)

See Also

Primary event censored distribution functions `pprimarycensored()`, `rprimarycensored()`

Examples

```
# Example: Weibull distribution with uniform primary events
dprimarycensored(c(0.1, 0.5, 1), pweibull, shape = 1.5, scale = 2.0)

# Example: Weibull distribution with exponential growth primary events
dprimarycensored(
  c(0.1, 0.5, 1), pweibull,
  dprimary = dexpgrowth,
  dprimary_args = list(r = 0.2), shape = 1.5, scale = 2.0
)
```

expgrowth

Exponential growth distribution functions

Description

Density, distribution function, and random generation for the exponential growth distribution.

Usage

```
dexpgrowth(x, min = 0, max = 1, r, log = FALSE)
```

```
pexpgrowth(q, min = 0, max = 1, r, lower.tail = TRUE, log.p = FALSE)
```

```
rexprowth(n, min = 0, max = 1, r)
```


Arguments

<code>x, q</code>	Vector of quantiles.
<code>min</code>	Minimum value of the distribution range. Default is 0.
<code>max</code>	Maximum value of the distribution range. Default is 1.
<code>r</code>	Rate parameter for the exponential growth.
<code>log, log.p</code>	Logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	Logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.
<code>n</code>	Number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required.

Details

The exponential growth distribution is defined on the interval $[\text{min}, \text{max}]$ with rate parameter (r). Its probability density function (PDF) is:

$$f(x) = \frac{r \cdot \exp(r \cdot (x - \text{min}))}{\exp(r \cdot \text{max}) - \exp(r \cdot \text{min})}$$

The cumulative distribution function (CDF) is:

$$F(x) = \frac{\exp(r \cdot (x - \text{min})) - \exp(r \cdot \text{min})}{\exp(r \cdot \text{max}) - \exp(r \cdot \text{min})}$$

For random number generation, we use the inverse transform sampling method:

1. Generate $u \sim \text{Uniform}(0, 1)$
2. Set $F(x) = u$ and solve for x :

$$x = \text{min} + \frac{1}{r} \cdot \log(u \cdot (\exp(r \cdot \text{max}) - \exp(r \cdot \text{min})) + \exp(r \cdot \text{min}))$$

This method works because of the probability integral transform theorem, which states that if X is a continuous random variable with CDF $F(x)$, then $Y = F(X)$ follows a $\text{Uniform}(0, 1)$ distribution. Conversely, if U is a $\text{Uniform}(0, 1)$ random variable, then $F^{-1}(U)$ has the same distribution as X , where F^{-1} is the inverse of the CDF.

In our case, we generate u from $\text{Uniform}(0, 1)$, then solve $F(x) = u$ for x to get a sample from our exponential growth distribution. The formula for x is derived by algebraically solving the equation:

$$u = \frac{\exp(r \cdot (x - \text{min})) - \exp(r \cdot \text{min})}{\exp(r \cdot \text{max}) - \exp(r \cdot \text{min})}$$

When r is very close to 0 ($|r| < 1e - 10$), the distribution approximates a uniform distribution on $[\text{min}, \text{max}]$, and we use a simpler method to generate samples directly from this uniform distribution.

Value

dexpgrowth gives the density, pexpgrowth gives the distribution function, and rexprowth generates random deviates.

The length of the result is determined by n for rexprowth, and is the maximum of the lengths of the numerical arguments for the other functions.

Examples

```
x <- seq(0, 1, by = 0.1)
probs <- dexpgrowth(x, r = 0.2)
cumprobs <- pexpgrowth(x, r = 0.2)
samples <- rexprowth(100, r = 0.2)
```

<code>fitdistdoublecens</code>	<i>Fit a distribution to doubly censored data</i>
--------------------------------	---

Description

This function wraps the custom approach for fitting distributions to doubly censored data using `fitdistrplus` and `primarycensored`.

Usage

```
fitdistdoublecens(
  censdata,
  distr,
  pwindow = 1,
  D = Inf,
  dprimary = stats::dunif,
  dprimary_name = lifecycle::deprecated(),
  dprimary_args = list(),
  truncation_check_multiplier = 2,
  ...
)
```

Arguments

<code>censdata</code>	A data frame with columns 'left' and 'right' representing the lower and upper bounds of the censored observations. Unlike <code>fitdistrplus::fitdistcens()</code> NA is not supported for either the upper or lower bounds.
<code>distr</code>	A character string naming the distribution to be fitted.
<code>pwindow</code>	Primary event window
<code>D</code>	Maximum delay (truncation point). If finite, the distribution is truncated at D. If set to Inf, no truncation is applied. Defaults to Inf.

dprimary	Function to generate the probability density function (PDF) of primary event times. This function should take a value <code>x</code> and a <code>pwindow</code> parameter, and return a probability density. It should be normalized to integrate to 1 over <code>[0, pwindow]</code> . Defaults to a uniform distribution over <code>[0, pwindow]</code> . Users can provide custom functions or use helper functions like <code>dexpgrowth</code> for an exponential growth distribution. See <code>primary_dists.R</code> for examples. The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply <code>add_name_attribute()</code> to yield properly tagged functions if they wish to leverage analytical solutions.
dprimary_name	[Deprecated] this argument will be ignored in future versions; use <code>add_name_attribute()</code> on <code>dprimary</code> instead
dprimary_args	List of additional arguments to be passed to <code>dprimary</code> . For example, when using <code>dexpgrowth</code> , you would pass <code>list(min = 0, max = pwindow, r = 0.2)</code> to set the minimum, maximum, and rate parameters
truncation_check_multiplier	Numeric multiplier to use for checking if the truncation time <code>D</code> is appropriate relative to the maximum delay. Set to <code>NULL</code> to skip the check. Default is 2.
...	Additional arguments to be passed to <code>fitdistrplus::fitdist()</code> .

Details

This function temporarily assigns and then removes functions from the global environment in order to work with `fitdistr`. Users should be aware of this behaviour, especially if they have existing functions with the same names in their global environment.

Value

An object of class "fitdist" as returned by `fitdistrplus::fitdist`.

See Also

Modelling wrappers for external fitting packages `pcd_as_stan_data()`, `pcd_cmdstan_model()`

Examples

```
# Example with normal distribution
set.seed(123)
n <- 1000
true_mean <- 5
true_sd <- 2
pwindow <- 2
swindow <- 2
D <- 10
samples <- rprimarycensored(
  n, rnorm,
  mean = true_mean, sd = true_sd,
  pwindow = pwindow, swindow = swindow, D = D
)
```

```

delay_data <- data.frame(
  left = samples,
  right = samples + swindow
)

fit_norm <- fitdistdoublecens(
  delay_data,
  distr = "norm",
  start = list(mean = 0, sd = 1),
  D = D, pwindow = pwindow
)

summary(fit_norm)

```

new_pcens

S3 class for primary event censored distribution computation

Description

S3 class for primary event censored distribution computation

Usage

```

new_pcens(
  pdist,
  dprimary,
  dprimary_args,
  pdist_name = lifecycle::deprecated(),
  dprimary_name = lifecycle::deprecated(),
  ...
)

```

Arguments

pdist	Distribution function (CDF). The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply add_name_attribute() to yield properly tagged functions if they wish to leverage the analytical solutions.
dprimary	Function to generate the probability density function (PDF) of primary event times. This function should take a value x and a <code>pwindow</code> parameter, and return a probability density. It should be normalized to integrate to 1 over $[0, \text{pwindow}]$. Defaults to a uniform distribution over $[0, \text{pwindow}]$. Users can provide custom functions or use helper functions like <code>dexpgrowth</code> for an exponential growth distribution. See <code>primary_dists.R</code> for examples. The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply add_name_attribute() to yield properly tagged functions if they wish to leverage analytical solutions.

dprimary_args	List of additional arguments to be passed to dprimary. For example, when using dexpgrowth, you would pass <code>list(min = 0, max = pwindow, r = 0.2)</code> to set the minimum, maximum, and rate parameters
pdist_name	[Deprecated] this argument will be ignored in future versions; use <code>add_name_attribute()</code> on pdist instead
dprimary_name	[Deprecated] this argument will be ignored in future versions; use <code>add_name_attribute()</code> on dprimary instead
...	Additional arguments to be passed to pdist

Value

An object of class `pcens_{pdist_name}_{dprimary_name}`. This contains the primary event distribution, the delay distribution, the delay distribution arguments, and any additional arguments. It can be used with the `pcens_cdf()` function to compute the primary event censored cdf.

See Also

Low level primary event censored distribution objects and methods `pcens_cdf()`, `pcens_cdf.default()`, `pcens_cdf.pcens_pgamma_dunif()`, `pcens_cdf.pcens_plnorm_dunif()`, `pcens_cdf.pcens_pweibull_dunif()`

pcd_as_stan_data	<i>Prepare data for primarycensored Stan model</i>
------------------	--

Description

This function takes in delay data and prepares it for use with the primarycensored Stan model.

Usage

```
pcd_as_stan_data(
  data,
  delay = "delay",
  delay_upper = "delay_upper",
  n = "n",
  pwindow = "pwindow",
  relative_obs_time = "relative_obs_time",
  dist_id,
  primary_id,
  param_bounds,
  primary_param_bounds,
  priors,
  primary_priors,
  compute_log_lik = FALSE,
  use_reduce_sum = FALSE,
  truncation_check_multiplier = 2
)
```

Arguments

<code>data</code>	A data frame containing the delay data.
<code>delay</code>	Column name for observed delays (default: "delay")
<code>delay_upper</code>	Column name for upper bound of delays (default: "delay_upper")
<code>n</code>	Column name for count of observations (default: "n")
<code>pwindow</code>	Column name for primary window (default: "pwindow")
<code>relative_obs_time</code>	Column name for relative observation time (default: "relative_obs_time")
<code>dist_id</code>	Integer identifying the delay distribution: You can use <code>pcd_stan_dist_id()</code> to get the dist ID for a distribution or look at the <code>pcd_distributions</code> data set.
<code>primary_id</code>	Integer identifying the primary distribution: You can use <code>pcd_stan_dist_id()</code> to get the primary dist ID for a distribution (make sure to select the "primary" type) or look at the <code>pcd_primary_distributions</code> data set.
<code>param_bounds</code>	A list with elements lower and upper, each a numeric vector specifying bounds for the delay distribution parameters.
<code>primary_param_bounds</code>	A list with elements lower and upper, each a numeric vector specifying bounds for the primary distribution parameters.
<code>priors</code>	A list with elements location and scale, each a numeric vector specifying priors for the delay distribution parameters.
<code>primary_priors</code>	A list with elements location and scale, each a numeric vector specifying priors for the primary distribution parameters.
<code>compute_log_lik</code>	Logical; compute log likelihood? (default: FALSE)
<code>use_reduce_sum</code>	Logical; use reduce_sum for performance? (default: FALSE)
<code>truncation_check_multiplier</code>	Numeric multiplier to use for checking if the truncation time D is appropriate relative to the maximum delay for each unique D value. Set to NULL to skip the check. Default is 2.

Value

A list containing the data formatted for use with `pcd_cmdstan_model()`

See Also

Modelling wrappers for external fitting packages `fitdistdoublecens()`, `pcd_cmdstan_model()`

Examples

```
data <- data.frame(
  delay = c(1, 2, 3),
  delay_upper = c(2, 3, 4),
  n = c(10, 20, 15),
  pwindow = c(1, 1, 2),
```

```

    relative_obs_time = c(10, 10, 10)
  )
  stan_data <- pcd_as_stan_data(
    data,
    dist_id = 1,
    primary_id = 1,
    param_bounds = list(lower = c(0, 0), upper = c(10, 10)),
    primary_param_bounds = list(lower = numeric(0), upper = numeric(0)),
    priors = list(location = c(1, 1), scale = c(1, 1)),
    primary_priors = list(location = numeric(0), scale = numeric(0))
  )

```

pcd_cmdstan_model *Create a CmdStanModel with primarycensored Stan functions*

Description

This function creates a `CmdStanModel` object using the Stan model and functions from `primarycensored` and optionally includes additional user-specified Stan files.

Usage

```
pcd_cmdstan_model(include_paths = primarycensored::pcd_stan_path(), ...)
```

Arguments

`include_paths` Character vector of paths to include for Stan compilation. Defaults to the result of `pcd_stan_path()`.

`...` Additional arguments passed to `cmdstanr::cmdstan_model()`.

Details

The underlying Stan model (`pcens_model.stan`) supports various features:

- Multiple probability distributions for modeling delays
- Primary and secondary censoring
- Truncation
- Optional use of `reduce_sum` for improved performance (via within chain parallelism).
- Flexible prior specifications
- Optional computation of log-likelihood for model comparison

Value

A `CmdStanModel` object.

See Also

Modelling wrappers for external fitting packages [fitdistdoublecens\(\)](#), [pcd_as_stan_data\(\)](#)

Examples

```
if (!is.null(cmdstanr::cmdstan_version(error_on_NA = FALSE))) {
  model <- pcd_cmdstan_model(compile = FALSE)
  model
}
```

pcd_distributions *Supported delay distributions*

Description

A dataset containing information about the supported delay distributions in primarycensored. Includes both distributions with base R implementations and those only available in Stan. Distributions beyond these are not supported in the stan code but any user functions can be used in the R code.

Usage

```
pcd_distributions
```

Format

A data.frame with 17 rows and 4 columns:

name Distribution name

pdist R distribution function name (e.g. plnorm), NA if there is no base R implementation

aliases Alternative names/identifiers

stan_id Stan distribution ID used in the stan code

See Also

Utility functions for working with distributions [add_name_attribute\(\)](#), [pcd_dist_name\(\)](#), [pcd_primary_distributions](#)

pcd_dist_name *Get distribution function cdf or pdf name*

Description

Get distribution function cdf or pdf name

Usage

```
pcd_dist_name(name, type = c("delay", "primary"))
```


Arguments

name	String. Distribution name or alias
type	String. "delay" or "primary" corresponding to the type of distribution to use as the look up. If delay then pcd_distributions() is used, if primary then pcd_primary_distributions() is used.

Value

String distribution function name or NA if no base R implementation

See Also

Utility functions for working with distributions [add_name_attribute\(\)](#), [pcd_distributions](#), [pcd_primary_distributions](#)

Examples

```
pcd_dist_name("lnorm")
pcd_dist_name("lognormal")
pcd_dist_name("gamma")
pcd_dist_name("weibull")
pcd_dist_name("exp")
pcd_dist_name("unif", type = "primary")
pcd_dist_name("expgrowth", type = "primary")
```

pcd_load_stan_functions

Load Stan functions as a string

Description

Load Stan functions as a string

Usage

```
pcd_load_stan_functions(  
  functions = NULL,  
  stan_path = primarycensored::pcd_stan_path(),  
  wrap_in_block = FALSE,  
  write_to_file = FALSE,  
  output_file = "pcd_functions.stan"  
)
```

Arguments

<code>functions</code>	Character vector of function names to load. Defaults to all functions.
<code>stan_path</code>	Character string, the path to the Stan code. Defaults to the path to the Stan code in the primarycensored package.
<code>wrap_in_block</code>	Logical, whether to wrap the functions in a <code>functions{}</code> block. Default is FALSE.
<code>write_to_file</code>	Logical, whether to write the output to a file. Default is FALSE.
<code>output_file</code>	Character string, the path to write the output file if <code>write_to_file</code> is TRUE. Defaults to "pcd_functions.stan".

Value

A character string containing the requested Stan functions

See Also

Tools for working with package Stan functions [pcd_stan_dist_id\(\)](#), [pcd_stan_files\(\)](#), [pcd_stan_functions\(\)](#), [pcd_stan_path\(\)](#)

`pcd_primary_distributions`

Supported primary event distributions

Description

A dataset containing information about the supported primary event distributions in primarycensored. Distributions beyond these are not supported in the stan code but any user functions can be used in the R code.

Usage

```
pcd_primary_distributions
```

Format

A data.frame with 2 rows and 4 columns:

name Distribution name
dprimary R density function name
aliases Alternative names/identifiers
stan_id Stan distribution ID used in the stan code

See Also

Utility functions for working with distributions [add_name_attribute\(\)](#), [pcd_dist_name\(\)](#), [pcd_distributions](#)

pcd_stan_dist_id *Get distribution stan ID by name*

Description

Get distribution stan ID by name

Usage

```
pcd_stan_dist_id(name, type = c("delay", "primary"))
```

Arguments

name	String. Distribution name or alias
type	String. "delay" or "primary" corresponding to the type of distribution to use as the look up. If delay then pcd_distributions() is used, if primary then pcd_primary_distributions() is used.

Value

Numeric distribution ID

See Also

Tools for working with package Stan functions [pcd_load_stan_functions\(\)](#), [pcd_stan_files\(\)](#), [pcd_stan_functions\(\)](#), [pcd_stan_path\(\)](#)

Examples

```
pcd_stan_dist_id("lnorm")
pcd_stan_dist_id("lognormal")
pcd_stan_dist_id("gamma")
pcd_stan_dist_id("weibull")
pcd_stan_dist_id("exp")
pcd_stan_dist_id("unif", type = "primary")
```

pcd_stan_files *Get Stan files containing specified functions*

Description

This function retrieves Stan files from a specified directory, optionally filtering for files that contain specific functions.

Usage

```
pcd_stan_files(functions = NULL, stan_path = primarycensored::pcd_stan_path())
```

Arguments

functions	Character vector of function names to search for. If NULL, all Stan files are returned.
stan_path	Character string specifying the path to the directory containing Stan files. Defaults to the Stan path of the primarycensored package.

Value

A character vector of file paths to Stan files.

See Also

Tools for working with package Stan functions [pcd_load_stan_functions\(\)](#), [pcd_stan_dist_id\(\)](#), [pcd_stan_functions\(\)](#), [pcd_stan_path\(\)](#)

pcd_stan_functions *Get Stan function names from Stan files*

Description

This function reads all Stan files in the specified directory and extracts the names of all functions defined in those files.

Usage

```
pcd_stan_functions(stan_path = primarycensored::pcd_stan_path())
```

Arguments

stan_path	Character string specifying the path to the directory containing Stan files. Defaults to the Stan path of the primarycensored package.
-----------	--

Value

A character vector containing unique names of all functions found in the Stan files.

See Also

Tools for working with package Stan functions [pcd_load_stan_functions\(\)](#), [pcd_stan_dist_id\(\)](#), [pcd_stan_files\(\)](#), [pcd_stan_path\(\)](#)

pcd_stan_path	<i>Get the path to the Stan code</i>
---------------	--------------------------------------

Description

Get the path to the Stan code

Usage

```
pcd_stan_path()
```

Value

A character string with the path to the Stan code

See Also

Tools for working with package Stan functions [pcd_load_stan_functions\(\)](#), [pcd_stan_dist_id\(\)](#), [pcd_stan_files\(\)](#), [pcd_stan_functions\(\)](#)

pcens_cdf	<i>Compute primary event censored CDF</i>
-----------	---

Description

This function dispatches to either analytical solutions (if available) or numerical integration via the default method. To see which combinations have analytical solutions implemented, use `methods(pcens_cdf)`. For example, `pcens_cdf$gamma_unif` indicates an analytical solution exists for gamma delay with uniform primary event distributions.

Usage

```
pcens_cdf(object, q, pwindow, use_numeric = FALSE)
```

Arguments

<code>object</code>	A primarycensored object as created by new_pcens() .
<code>q</code>	Vector of quantiles
<code>pwindow</code>	Primary event window
<code>use_numeric</code>	Logical, if TRUE forces use of numeric integration even for distributions with analytical solutions. This is primarily useful for testing purposes or for settings where the analytical solution breaks down.

Value

Vector of computed primary event censored CDFs

See Also

Low level primary event censored distribution objects and methods [new_pcens\(\)](#), [pcens_cdf.default\(\)](#), [pcens_cdf.pcens_pgamma_dunif\(\)](#), [pcens_cdf.pcens_plnorm_dunif\(\)](#), [pcens_cdf.pcens_pweibull_dunif\(\)](#)

pcens_cdf.default *Default method for computing primary event censored CDF*

Description

This method serves as a fallback for combinations of delay and primary event distributions that don't have specific implementations. It uses a numeric integration method.

Usage

```
## Default S3 method:
pcens_cdf(object, q, pwindow, use_numeric = FALSE)
```

Arguments

object	A primarycensored object as created by new_pcens() .
q	Vector of quantiles
pwindow	Primary event window
use_numeric	Logical, if TRUE forces use of numeric integration even for distributions with analytical solutions. This is primarily useful for testing purposes or for settings where the analytical solution breaks down.

Details

This method implements the numerical integration approach for computing the primary event censored CDF. It uses the same mathematical formulation as described in the details section of [pprimarycensored\(\)](#), but applies numerical integration instead of analytical solutions.

Value

Vector of computed primary event censored CDFs

See Also

[pprimarycensored\(\)](#) for the mathematical details of the primary event censored CDF computation.

Low level primary event censored distribution objects and methods [new_pcens\(\)](#), [pcens_cdf\(\)](#), [pcens_cdf.pcens_pgamma_dunif\(\)](#), [pcens_cdf.pcens_plnorm_dunif\(\)](#), [pcens_cdf.pcens_pweibull_dunif\(\)](#)

 pcens_cdf.pcens_pgamma_dunif

Method for Gamma delay with uniform primary

Description

Method for Gamma delay with uniform primary

Usage

```
## S3 method for class 'pcens_pgamma_dunif'
pcens_cdf(object, q, pwindow, use_numeric = FALSE)
```

Arguments

object	A primarycensored object as created by new_pcens() .
q	Vector of quantiles
pwindow	Primary event window
use_numeric	Logical, if TRUE forces use of numeric integration even for distributions with analytical solutions. This is primarily useful for testing purposes or for settings where the analytical solution breaks down.

Value

Vector of computed primary event censored CDFs

See Also

Low level primary event censored distribution objects and methods [new_pcens\(\)](#), [pcens_cdf\(\)](#), [pcens_cdf.default\(\)](#), [pcens_cdf.pcens_plnorm_dunif\(\)](#), [pcens_cdf.pcens_pweibull_dunif\(\)](#)

 pcens_cdf.pcens_plnorm_dunif

Method for Log-Normal delay with uniform primary

Description

Method for Log-Normal delay with uniform primary

Usage

```
## S3 method for class 'pcens_plnorm_dunif'
pcens_cdf(object, q, pwindow, use_numeric = FALSE)
```

Arguments

object	A primarycensored object as created by new_pcens() .
q	Vector of quantiles
pwindow	Primary event window
use_numeric	Logical, if TRUE forces use of numeric integration even for distributions with analytical solutions. This is primarily useful for testing purposes or for settings where the analytical solution breaks down.

Value

Vector of computed primary event censored CDFs

See Also

Low level primary event censored distribution objects and methods [new_pcens\(\)](#), [pcens_cdf\(\)](#), [pcens_cdf.default\(\)](#), [pcens_cdf.pcens_pgamma_dunif\(\)](#), [pcens_cdf.pcens_pweibull_dunif\(\)](#)

pcens_cdf.pcens_pweibull_dunif

Method for Weibull delay with uniform primary

Description

Method for Weibull delay with uniform primary

Usage

```
## S3 method for class 'pcens_pweibull_dunif'
pcens_cdf(object, q, pwindow, use_numeric = FALSE)
```

Arguments

object	A primarycensored object as created by new_pcens() .
q	Vector of quantiles
pwindow	Primary event window
use_numeric	Logical, if TRUE forces use of numeric integration even for distributions with analytical solutions. This is primarily useful for testing purposes or for settings where the analytical solution breaks down.

Value

Vector of computed primary event censored CDFs

See Also

Low level primary event censored distribution objects and methods [new_pcens\(\)](#), [pcens_cdf\(\)](#), [pcens_cdf.default\(\)](#), [pcens_cdf.pcens_pgamma_dunif\(\)](#), [pcens_cdf.pcens_plnorm_dunif\(\)](#)

pprimarycensored *Compute the primary event censored CDF for delays*

Description

This function computes the primary event censored cumulative distribution function (CDF) for a given set of quantiles. It adjusts the CDF of the primary event distribution by accounting for the delay distribution and potential truncation at a maximum delay (D). The function allows for custom primary event distributions and delay distributions.

Usage

```
pprimarycensored(  
  q,  
  pdist,  
  pwindow = 1,  
  D = Inf,  
  dprimary = stats::dunif,  
  dprimary_args = list(),  
  pdist_name = lifecycle::deprecated(),  
  dprimary_name = lifecycle::deprecated(),  
  ...  
)  
  
ppcens(  
  q,  
  pdist,  
  pwindow = 1,  
  D = Inf,  
  dprimary = stats::dunif,  
  dprimary_args = list(),  
  pdist_name = lifecycle::deprecated(),  
  dprimary_name = lifecycle::deprecated(),  
  ...  
)
```

Arguments

q	Vector of quantiles
pdist	Distribution function (CDF). The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply <code>add_name_attribute()</code> to yield properly tagged functions if they wish to leverage the analytical solutions.
pwindow	Primary event window
D	Maximum delay (truncation point). If finite, the distribution is truncated at D. If set to Inf, no truncation is applied. Defaults to Inf.

dprimary	Function to generate the probability density function (PDF) of primary event times. This function should take a value x and a <code>pwindow</code> parameter, and return a probability density. It should be normalized to integrate to 1 over $[0, pwindow]$. Defaults to a uniform distribution over $[0, pwindow]$. Users can provide custom functions or use helper functions like <code>dexpgrowth</code> for an exponential growth distribution. See <code>primary_dists.R</code> for examples. The package can identify base R distributions for potential analytical solutions. For non-base R functions, users can apply <code>add_name_attribute()</code> to yield properly tagged functions if they wish to leverage analytical solutions.
dprimary_args	List of additional arguments to be passed to <code>dprimary</code> . For example, when using <code>dexpgrowth</code> , you would pass <code>list(min = 0, max = pwindow, r = 0.2)</code> to set the minimum, maximum, and rate parameters
pdist_name	[Deprecated] this argument will be ignored in future versions; use <code>add_name_attribute()</code> on <code>pdist</code> instead
dprimary_name	[Deprecated] this argument will be ignored in future versions; use <code>add_name_attribute()</code> on <code>dprimary</code> instead
...	Additional arguments to be passed to <code>pdist</code>

Details

The primary event censored CDF is computed by integrating the product of the delay distribution function (CDF) and the primary event distribution function (PDF) over the primary event window. The integration is adjusted for truncation if a finite maximum delay (D) is specified.

The primary event censored CDF, $F_{\text{cens}}(q)$, is given by:

$$F_{\text{cens}}(q) = \int_0^{pwindow} F(q-p) \cdot f_{\text{primary}}(p) dp$$

where F is the CDF of the delay distribution, f_{primary} is the PDF of the primary event times, and $pwindow$ is the primary event window.

If the maximum delay D is finite, the CDF is normalized by dividing by $F_{\text{cens}}(D)$:

$$F_{\text{cens, norm}}(q) = \frac{F_{\text{cens}}(q)}{F_{\text{cens}}(D)}$$

where $F_{\text{cens, norm}}(q)$ is the normalized CDF.

This function creates a `primarycensored` object using `new_pcens()` and then computes the primary event censored CDF using `pcens_cdf()`. This abstraction allows for automatic use of analytical solutions when available, while seamlessly falling back to numerical integration when necessary.

See `methods(pcens_cdf)` for which combinations have analytical solutions implemented.

Value

Vector of primary event censored CDFs, normalized by D if finite (truncation adjustment)

See Also

[new_pcens\(\)](#) and [pcens_cdf\(\)](#)

Primary event censored distribution functions [dprimarycensored\(\)](#), [rprimarycensored\(\)](#)

Examples

```
# Example: Lognormal distribution with uniform primary events
pprimarycensored(c(0.1, 0.5, 1), plnorm, meanlog = 0, sdlog = 1)

# Example: Lognormal distribution with exponential growth primary events
pprimarycensored(
  c(0.1, 0.5, 1), plnorm,
  dprimary = dexpgrowth,
  dprimary_args = list(r = 0.2), meanlog = 0, sdlog = 1
)
```

<code>rprimarycensored</code>	<i>Generate random samples from a primary event censored distribution</i>
-------------------------------	---

Description

This function generates random samples from a primary event censored distribution. It adjusts the distribution by accounting for the primary event distribution and potential truncation at a maximum delay (D). The function allows for custom primary event distributions and delay distributions.

Usage

```
rprimarycensored(
  n,
  rdist,
  pwindow = 1,
  swindow = 1,
  D = Inf,
  rprimary = stats::runif,
  rprimary_args = list(),
  oversampling_factor = 1.2,
  ...
)

rpcens(
  n,
  rdist,
  pwindow = 1,
  swindow = 1,
  D = Inf,
  rprimary = stats::runif,
  rprimary_args = list(),

```

```
oversampling_factor = 1.2,
...
)
```

Arguments

n	Number of random samples to generate.
rdist	Function to generate random samples from the delay distribution for example <code>stats::rlnorm()</code> for lognormal distribution.
pwindow	Primary event window
swindow	Integer specifying the window size for rounding the delay (default is 1). If <code>swindow = 0</code> then no rounding is applied.
D	Maximum delay (truncation point). If finite, the distribution is truncated at D. If set to Inf, no truncation is applied. Defaults to Inf.
rprimary	Function to generate random samples from the primary distribution (default is <code>stats::runif()</code>).
rprimary_args	List of additional arguments to be passed to rprimary.
oversampling_factor	Factor by which to oversample the number of samples to account for truncation (default is 1.2).
...	Additional arguments to be passed to the distribution function.

Details

The mathematical formulation for generating random samples from a primary event censored distribution is as follows:

1. Generate primary event times (p) from the specified primary event distribution (f_p) with parameters ϕ , defined between 0 and the primary event window ($pwindow$):

$$p \sim f_p(\phi), \quad p \in [0, pwindow]$$

2. Generate delays (d) from the specified delay distribution (f_d) with parameters θ :

$$d \sim f_d(\theta)$$

3. Calculate the total delays (t) by adding the primary event times and the delays:

$$t = p + d$$

4. Apply truncation (i.e. remove any delays that fall outside the observation window) to ensure that the delays are within the specified range $[0, D]$, where D is the maximum observable delay:

$$t_{truncated} = \{t \mid 0 \leq t < D\}$$

5. Round the truncated delays to the nearest secondary event window ($swindow$):

$$t_{valid} = \lfloor \frac{t_{truncated}}{swindow} \rfloor \times swindow$$

The function oversamples to account for potential truncation and generates additional samples if needed to reach the desired number of valid samples.

Value

Vector of random samples from the primary event censored distribution censored by the secondary event window.

See Also

Primary event censored distribution functions [dprimarycensored\(\)](#), [pprimarycensored\(\)](#)

Examples

```
# Example: Lognormal distribution with uniform primary events
rprimarycensored(10, rlnorm, meanlog = 0, sdlog = 1)

# Example: Lognormal distribution with exponential growth primary events
rprimarycensored(
  10, rlnorm,
  rprimary = rexprowth, rprimary_args = list(r = 0.2),
  meanlog = 0, sdlog = 1
)
```

Index

- * **check**
 - check_dprimary, 4
 - check_pdist, 5
 - check_truncation, 5
 - * **datasets**
 - pcd_distributions, 16
 - pcd_primary_distributions, 18
 - * **modelhelpers**
 - fitdistdoublecens, 10
 - pcd_as_stan_data, 13
 - pcd_cmdstan_model, 15
 - * **pcens**
 - new_pcens, 12
 - pcens_cdf, 21
 - pcens_cdf.default, 22
 - pcens_cdf.pcens_pgamma_dunif, 23
 - pcens_cdf.pcens_plnorm_dunif, 23
 - pcens_cdf.pcens_pweibull_dunif, 24
 - * **primarycensored**
 - dprimarycensored, 6
 - rprimarycensored, 25
 - rprimarycensored, 27
 - * **primaryeventdistributions**
 - expgrowth, 8
 - * **stantools**
 - pcd_load_stan_functions, 17
 - pcd_stan_dist_id, 19
 - pcd_stan_files, 19
 - pcd_stan_functions, 20
 - pcd_stan_path, 21
 - * **utils**
 - add_name_attribute, 3
 - pcd_dist_name, 16
 - pcd_distributions, 16
 - pcd_primary_distributions, 18
- add_name_attribute, 3, 16–18
- add_name_attribute(), 4, 5, 7, 11–13, 25, 26
- check_dprimary, 4, 5, 6
- check_pdist, 4, 5, 6
- check_truncation, 4, 5, 5
- dexpgrowth (expgrowth), 8
- dpcens (dprimarycensored), 6
- dprimarycensored, 6, 27, 29
- expgrowth, 8
- fitdistdoublecens, 10, 14, 15
- fitdistrplus::fitdist(), 11
- fitdistrplus::fitdistcens(), 10
- new_pcens, 12, 22–24
- new_pcens(), 21–24, 26, 27
- pcd_as_stan_data, 11, 13, 15
- pcd_cmdstan_model, 11, 14, 15
- pcd_cmdstan_model(), 14
- pcd_dist_name, 3, 16, 16, 18
- pcd_dist_name(), 3
- pcd_distributions, 3, 14, 16, 17, 18
- pcd_distributions(), 17, 19
- pcd_load_stan_functions, 17, 19–21
- pcd_primary_distributions, 3, 14, 16, 17, 18
- pcd_primary_distributions(), 17, 19
- pcd_stan_dist_id, 18, 19, 20, 21
- pcd_stan_dist_id(), 14
- pcd_stan_files, 18, 19, 19, 20, 21
- pcd_stan_functions, 18–20, 20, 21
- pcd_stan_path, 18–20, 21
- pcens_cdf, 13, 21, 22–24
- pcens_cdf(), 26, 27
- pcens_cdf.default, 13, 22, 22, 23, 24
- pcens_cdf.pcens_pgamma_dunif, 13, 22, 23, 24
- pcens_cdf.pcens_plnorm_dunif, 13, 22, 23, 23, 24
- pcens_cdf.pcens_pweibull_dunif, 13, 22–24, 24

pexpgrowth (expgrowth), 8
ppcens (pprimarycensored), 25
pprimarycensored, 8, 25, 29
pprimarycensored(), 3, 8, 22

rexprowth (expgrowth), 8
rpcens (rprimarycensored), 27
rprimarycensored, 8, 27, 27

stats::rlnorm(), 28
stats::runif(), 28